Use one computer to display the same high-resolution image on numerous monitors: up to 256

- Supports VGA/SVGA UXGA/WUXGA monitors, including LCD flat panel monitors.
- 1900x1200 resolution with no degradation.
- Supports the DDC2B protocol.
- Burn-in monitors after repair.
- Ideal for classrooms, tradeshows, or digital signage where high quality video on multiple monitors is needed.



#### **VOPEX-8V-H VGA Video Splitter (Front & Back)**

The VOPEX® VGA Video Splitter enables up to eight VGA monitors to be driven by a single computer. The same image can be displayed on up to 256 monitors by cascading. The DDC2B protocol is supported from Output-1.

# **Specifications**

## **Video Input**

- Male 15-pin HD input connector.
- Supports a PC, SUN or MAC with VGA video.
- Multiplatform support: Windows 2000/XP/Vista/7/8/10, Windows Server 2000/2003/2008/2012/2016/2019, Solaris, Linux, FreeBSD, and MAC OS 9/10.
- Maximum input levels for video: 1.45Vp-p.
- Input impedance: 75 Ohms.
- Supports Separate and Composite TTL level sync and Sync On Green.
- Sync input frequency ranges:
  Horizontal: 15 to 130 kHz.
  Vertical: 30 to 150 Hz.

#### **Video Output**

- Female 15-pin HD output connectors.
- Crisp and clear 1900x1200 resolution.
- Bandwidth is 150 MHz.
- Maximum output levels for video: 1.45Vp-p.
- Output impedance: 75 Ohms.
- All outputs are individually buffered.
- All monitors must be able to support the highest resolution of the DDC monitor connected to Output-1.

#### **Environmental**

- Operating temperature: 32 to 100°F (0 to 38°C)
- Storage temperature: -20 to 140°F (-30 to 60°C)
- Operating and Storage Relative Humidity: 17 to 90% non-condensing RH.

#### **Power**

■ 1110 or 220 VAC at 50 or 60 Hz.

Power Consumption					
Model	Power (W)	Model	Power (W)		
VOPEX-2V-H	5	VOPEX-4V-H	5		
VOPEX-8V-H	5				

MTBF					
NTI Part #	MTBF (hrs)	NTI Part #	MTBF (hrs)		
VOPEX-2V-H	175,784	VOPEX-4V-H	153,392		
VOPEX-8V-H	135,708				

### **Regulatory Approvals**

RoHS

## **Cables**

- Extend 1900x1200 resolution to 50 feet (15 meters), and 1600x1200 to 100 feet (488x366 to 30 meters) with no degradation using NTI's VEXT-xx cables.
- 3-foot (0.91-meter) VGA cable included.

# Use one computer to display the same high-resolution image on numerous monitors: up to 256

VGA Video Splitter Models				
NTI Part #	# of Ports	Size WxDxH (in.)		
VOPEX-2V-H	2	4.9x5.2x1.7		
VOPEX-4V-H	4	8x6.2x2.6		
VOPEX-8V-H	8	8x6.2x2.6		

# **Configuration and Cable Illustration**

