

## Allows two users to control one USB computer and connect three USB devices

- Compatible with USB computers (PC, SUN, MAC).
- Built-in hub for multiple USB devices.
- Access one computer from two locations.
- Two users can enter data into the same program.
- Compliant with USB 1.1 (low/full speed) standards.
- Supports Plug-n-Play specifications.
- Supports international keyboard layouts in auto-detection mode.
- High quality, rugged steel construction with durable powder coat finish.
- Meets the electrostatic discharge (ESD) immunity requirements of IEC/EN 61000-4-2.



**VOPEX-USBV-2 (Front & Back)**

The VOPEX® VGA USB KVM Splitter with built-in USB hub allows two users (two USB keyboards, mice and VGA monitors) to access one USB computer (PC, SUN, MAC) and up to three USB devices (printers, scanners, security cameras, etc).

## Specifications

### Hosts

- Male 15-pin HD connector.
- Female USB Type B connector.
- Supports a USB computer (PC, SUN, MAC).
- Multiplatform support: Windows 7/8/10, Windows Server 2008/2012/2016/2019, Solaris, Linux, FreeBSD, and MAC OS 10/11.

### Monitor

- Female 15-pin HD connectors.
- Crisp and clear 1920x1200 resolution.
- Bandwidth is 150 MHz.

### Devices

- Female USB Type A connectors for connection of keyboards and mice.
  - Compatible with most USB keyboards and mice, including Microsoft USB Intellimouse®, Logitech Cordless Elite Duo keyboard and mouse, Gyration keyboard/mouse and Crystal Vision keyboard with touchpad.
  - Keyboard and mouse are hot-pluggable.
- Three female USB Type A connectors for connection of USB peripheral devices (printers, scanners, security cameras, bar code scanners, etc.).
  - Use to connect Motorola Symbol LS3408 bar code scanners.
  - Does not support USB touchscreen monitors.
- Provides support for full-speed (12 Mbps) or low-speed (1.5 Mbps) USB devices.

### Power

- 110 or 220 VAC at 50 or 60 Hz via AC adapter.
- Country-specific AC adapter included

### MTBF

- VOPEX-USBV-2: 79,077 hrs

### Dimensions

- WxDxH (in): 8.5x6.0x2.6 in. (216x152x66 mm)

### Environmental

- Operating temperature: 32°F to 100°F (0°C to 38°C).
- Storage temperature: -22°F to 140°F (-30°C to 60°C).
- Operating and storage relative humidity: 5 to 90% non-condensing RH.

### Regulatory Approvals

- CE, RoHS
- TAA compliant

### Warranty

- Two years.

### Cables

- One 3-foot (0.9-meter) female 15HD to male 15HD cable included.
- One 3.2-foot (1-meter) male USB Type B to male USB Type A cable included.

## Control Modes

- Press Mode button to cycle through all four modes. LEDs indicate which mode is selected.
- User 1 Mode - Only User 1 can type or move the mouse.
- User 2 Mode - Only User 2 can type or move the mouse.
- Inst Mode - Keyboard or mouse activates immediately.
- Delay Mode - Locked out user must wait five seconds after last keystroke or mouse movement occurs on active user.

