

1 m (3.3 ft.) USB-C to Mini DisplayPort Cable - 4K 60Hz - Black

Product ID: CDP2MDPMM1MB



This USB-C to Mini DisplayPort cable lets you connect your Thunderbolt 3 or USB Type-C enabled device to a Mini DP monitor with just one cable, for a convenient, clutter-free connection.

Harness the video capabilities that are built into your USB-C connection. The USB Type-C to Mini DisplayPort cable delivers the astonishing quality of Ultra HD to your 4K display, at resolutions up to 3840 x 2160. Plus, the adapter is backward compatible with 1080p displays, which makes it a great accessory for home, office or other work environments.

At 1 m (3.3 ft.) in length, this Mini DP cable delivers a compact connection that eliminates excess adapters and cabling, ensuring a tidy, professional installation. For longer installations, we also offer a 6 ft. (1.8 m) USB-C to mDP cable, enabling you to choose the right cable length for your custom installation needs.

For easy operation and installation, this USB 3.1 Type-C to Mini DP adapter cable supports plug-and-play installation on both Windows and Mac computers.

CDP2MDPMM1MB is backed by a 3-year StarTech.com warranty and free lifetime technical support.

Certifications, Reports and Compatibility

Applications

- Connect your MacBook or USB-C device to an mDP monitor
- Ideal for home office or hot desk environments
- Experience crisp visuals with support for 4K 60Hz
- Deliver enriched presentations on the go

Features

- Reduce clutter with a USB-C to mDP adapter and cable in one
- Get astonishing picture quality with support for UHD video resolutions up to 4K 60Hz
- Make the perfect connection with a Mini DisplayPort cable that works with any USB Type-C enabled device
- Hassle-free connectivity with the reversible USB-C connector
- Compatible with Thunderbolt 3 and USB 3.1 Type-C ports that support DP Alt Mode

Hardware

| | |
|------------|------------------------------------|
| Warranty | 3 Years |
| Ports | 1 |
| AV Input | USB-C |
| AV Output | Mini DisplayPort - 1.2 |
| Chipset ID | STMicroelectronics - STM32F072CBU6 |

Performance

| | |
|-----------------------------|--|
| Maximum Digital Resolutions | 3840x2160 @ 60 Hz |
| Supported Resolutions | 1024x768 1280x720 (High-definition 720p) 1920x1080 (High-definition 1080p) 1920x1200 2560x1440 2560x1600 3840x2160 (Ultra HD 4K) |
| Wide Screen Supported | Yes |
| Audio Specifications | DisplayPort - 5.1 Channel Audio |

Connector(s)

| | |
|-------------|-------------------------------------|
| Connector A | USB-C (24 pin) DisplayPort Alt Mode |
| Connector B | Mini-DisplayPort (20 pin) |

Special Notes / Requirements

| | |
|------|---|
| Note | Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. |
|------|---|

Environmental



| | |
|-----------------------|---------------------------|
| Operating Temperature | 5C to 35C (41F to 95F) |
| Storage Temperature | -20C to 60C (-4F to 140F) |
| Humidity | 25%-60%RH |

Physical Characteristics

| | |
|-------------------|--------------------|
| Color | Black |
| Cable Length | 39.4 in [100 cm] |
| Product Length | 39.4 in [100.0 cm] |
| Product Width | 0.8 in [20.0 mm] |
| Product Height | 0.4 in [10.0 mm] |
| Weight of Product | 0.9 oz [25.0 g] |

Packaging Information

| | |
|---------------------------|------------------|
| Package Length | 8.7 in [22.0 cm] |
| Package Width | 7.9 in [20.0 cm] |
| Package Height | 0.5 in [12.0 mm] |
| Shipping (Package) Weight | 1.1 oz [30.5 g] |

What's in the Box

| | |
|---------------------|---------------------------------|
| Included in Package | USB-C to Mini DisplayPort cable |
|---------------------|---------------------------------|

****Product appearance and specifications are subject to change without notice.***

