

USB C Multiport Video Adapter w/ HDMI, VGA, Mini DisplayPort or DVI - USB Type C Monitor Adapter to HDMI 2.0 or mDP 1.2 (4K 60Hz) - VGA or DVI (1080p) - Space Gray Aluminum

Product ID: CDPVDHMDMP2G



This USB-C multiport video adapter offers a portable solution for connecting your USB Type-C laptop to a VGA, DVI, HDMI or Mini DisplayPort (mDP) display.

Avoid the hassle of carrying different adapters, with a 4-in-1 USB-C monitor adapter. With VGA, DVI, HDMI and mDP output, you can connect your laptop to any display using this multiport adapter.

The adapter features a magnetic retainer that guides the breakout cable into place for quick, secure portability. With a durable aluminum enclosure, the adapter can withstand being carried in your travel bag.

The HDMI and mDP outputs on this USB-C video adapter support UHD resolutions up to 4K 60Hz, while the VGA and DVI outputs support HD resolutions up to 1920 x 1200.

The USB-C adapter has a Space Gray housing and built-in USB-C cable designed to match your Space Gray MacBook, or MacBook Pro. The adapter is compatible with USB-C DP Alt Mode devices.

The adapter is also available with 4K 30Hz HDMI resolution support, in three colors: Space Gray (CDPVDHMDMP2G), Rose Gold (CDPVDHMDMPRG) and Silver (CDPVDHMDMP), so you can choose an adapter that matches your laptop or your color preference.

CDPVDHMDMP2G is backed by a StarTech.com 3-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility

Applications

- Connect to virtually any display while traveling

- Connect your MacBook to a provided VGA, DVI, HDMI or mDP display at work or school
- Connect a secondary VGA, DVI, HDMI or mDP monitor to your Space Gray MacBook

Features

- **4-IN-1 MULTIPORT USB-C VIDEO ADAPTER:** USB-C DP Alt Mode to any one of HDMI 2.0 (4K 60Hz & 7.1ch audio), mDP 1.2 (4K 60Hz & 2ch audio), VGA or DVI (1080p), HDCP 2.2/1.4, Thunderbolt 3 compatible
- **TOUGH & PORTABLE:** Durable aluminum space gray enclosure with a magnetically-secured hideaway cable wrap for on-the-go users in the office, at home, boardrooms, and classrooms
- **COMPATIBILITY:** USB-C display adapter for Dell XPS/Precision/Latitude, Lenovo ThinkPad X1 Carbon/Extreme, Surface 3, HP EliteBook/Spectre/ZBook, Chromebooks, TB3 MacBook Pro/Air [Note: The VGA output does not work with M1 based MacBook hosts]
- **TESTED & VERIFIED:** USB Type-C adapter tested @ 4K 60Hz mini DisplayPort/HDMI or 1080p VGA/DVI for compatibility w/ TV, monitor & projector brands like Dell, Asus, Acer, LG, Samsung, Sharp, Sony, Epson
- **EASY TO USE:** Supporting a driverless plug-and-play setup, this adapter is fully compatible with multiple OS platforms: Windows / macOS / Linux / Chrome OS

Hardware

Warranty	3 Years
Active or Passive Adapter	Active
AV Input	USB-C
AV Output	HDMI - 1.4 Mini DisplayPort - 1.2 DVI-I (Digital Only) - Single-Link VGA
Chipset ID	Cypress - CYPD3120 Parade - PS8348 Parade - PS8617 Parade - PS8338 Parade - PS171 Parade - PS176

Performance



Video Revision	HDMI 2.0 DisplayPort 1.2
Maximum Cable Distance To Display	49.9 ft [15.2 m]
Maximum Analog Resolutions	1920 x 1200 @ 60Hz
Maximum Digital Resolutions	4096 X 2160 @ 24Hz or 3840 X 2160 @ 60Hz (HDMI) 4096 X 2160 @ 60Hz (mDP)
Supported Resolutions	Maximum HDMI output: 4096 X 2160 @ 24Hz or 3840 X 2160 @ 60Hz Maximum mDP output: 4096 X 2160 @ 60Hz Maximum DVI and VGA output: 1920 x 1200 @ 60Hz <i><i>Lower resolutions and refresh rates may also be supported</i></i>
Wide Screen Supported	Yes
Audio Specifications	HDMI - 7.1 Channel Audio DVI - No Audio Support VGA - No Audio Support Mini DisplayPort - 5.1 Channel Audio
MTBF	800,703 hours

Connector(s)

Connector A	USB-C (24 pin) DisplayPort Alt Mode
Connector B	Mini-DisplayPort (20 pin) VGA (15 pin, High Density D-Sub) DVI-I (29 pin) HDMI (19 pin)



Special Notes / Requirements

Note	<p>Only one video output is supported on the video adapter at a time, if multiple connections are made, only one of the outputs will function</p> <p>Maximum Cable Distance to Display refers to digital video. VGA distance capabilities are dependent upon the quality of your cabling</p> <p>The VGA output does not work with M1, M1 PRO, and M1 MAX MacBook hosts</p>
------	--

Environmental

Operating Temperature	0C to 45C (32F to 113F)
Storage Temperature	-10C to 70C (14F to 158F)
Humidity	Storage: 5% ~ 90 % RH (no condensation) Operating: 10% ~ 85 % RH (no condensation)

Physical Characteristics

Color	Space Gray
Material	Aluminum
Cable Length	4.5 in [11.5 cm]
Product Length	6.9 in [17.5 cm]
Product Width	5.6 in [14.2 cm]
Product Height	1.2 in [30 mm]
Weight of Product	6.5 oz [185 g]

Packaging Information

Package Length	2.2 in [55 mm]
Package Width	4.1 in [10.5 cm]
Package Height	0.6 in [16 mm]
Shipping (Package) Weight	4.3 oz [121 g]



What's in the Box

Included in Package	travel A/V adapter
---------------------	--------------------

****Product appearance and specifications are subject to change without notice.***

