

USB-C Multiport Video Adapter - 3-in-1 - 4K 30Hz - Black

Product ID: CDPVGDVHDBP



This USB-C multiport video adapter offers a portable solution for connecting your USB Type-C laptop to a VGA, DVI or HDMI display.

Avoid the hassle of carrying different adapters for different displays with this 3-in-1 USB-C adapter. With VGA, DVI and HDMI output, you can connect your laptop to virtually any display.

The HDMI output on this USB-C video adapter supports UHD 4K resolutions, providing four times the picture quality of high-definition 1080p. All of the outputs (HDMI, VGA, DVI) can support high-definition resolutions of up to 1920 x 1200.

The convenient plug-and-play USB-C dongle is the perfect travel accessory. Fitting easily into your laptop bag, and offering three video output options, the USB-C display adapter is an ideal solution for Bring Your Own Device (BYOD) applications, wherever you go.

The CDPVGDVHDBP is backed by a StarTech.com 3-year warranty and free lifetime technical support.

## **Certifications, Reports and Compatibility**

## **Applications**

- · Connect to virtually any display while traveling
- Connect your BYOD laptop to a provided VGA, DVI or HDMI display at work or school
- · Connect a VGA, DVI or HDMI monitor to your USB-C computer to use as a secondary monitor

## **Features**



- Maximize your video compatibility with a 3-in-1 USB-C display adapter: USB-C to VGA, DVI, or HDMI
- Get astonishing picture quality with support for UHD resolutions up to 4K 30Hz
- Thunderbolt 3 and USB Type-C with DP Alt Mode Compatible

• Easy to set up, use, and store

**Hardware** 

Warranty 3 Years

Active or Passive Adapter Active

AV Input USB-C

AV Output HDMI - 1.4

DVI-I (Digital Only) - Single-Link

**VGA** 

**Performance** 

Video Revision DisplayPort 1.2

Maximum Cable Distance

To Display

49.9 ft [15.2 m]

Maximum Analog

Resolutions

1920 x 1200 @ 60Hz

Maximum Digital Resolutions

3840 x 2160 @ 30Hz

Supported Resolutions

HDMI output: 3840 x 2160 (@ 30 Hz), 2560 x 1600, 2048 x 1280

(@ 60 Hz), 1920 x 1200, 1920 x 1080, 1280 x 720

VGA and DVI output: 1920 x 1200 (@ 60 Hz), 1920 x 1080,

1280 x 720

Wide Screen Supported Yes

Audio Specifications HDMI - 7.1 Channel Audio

DVI - No Audio Support

VGA - No Audio Support

General Specifications Only one video output is supported on the video adapter at a



time. If multiple connections are made, only one of the outputs will function.

Connector(s)

Connector A USB-C (24 pin) DisplayPort Alt Mode

Connector B HDMI (19 pin)

DVI-I (29 pin)

VGA (15 pin, High Density D-Sub)

Special Notes / Requirements

> System and Cable Your USB-C port must support DisplayPort over USB-C (DP Alt Requirements

mode) in order to work with this adapter.

Note Maximum Cable Distance to Display refers to digital video. VGA

distance capabilities are dependent upon the quality of your

cabling

**Environmental** 

Operating Temperature 0C to 45C (32F to 113F)

Storage Temperature -10C to 70C (14F to 158F)

Humidity 10%-85% RH

**Physical** Characteristics

> Color Black

Cable Length 5.9 in [15 cm]

Product Length 3.3 in [85.0 mm]

Product Width 1.8 in [45.0 mm]

**Product Height** 0.6 in [15.0 mm]

Weight of Product 1.8 oz [51.0 g]

**Packaging** Information

> Package Length 8.9 in [22.5 cm]

> Package Width 4.9 in [12.5 cm]

Package Height 0.8 in [20.0 mm]



|                   | Shipping (Package)<br>Weight | 1.9 oz [55.0 g]      |
|-------------------|------------------------------|----------------------|
| What's in the Box | Included in Package          | USB-C travel adapter |

<sup>\*</sup>Product appearance and specifications are subject to change without notice.