

## USB 3.0 to DVI Adapter with 1-Port USB Hub – 1920x1200

**Product ID:** USB32DVIEH



The USB32DVIEH USB 3.0 to DVI Adapter is TAA compliant and turns an available USB 3.0 port into a DVI output port with high resolution 1920x1200 video support. The adapter features built-in USB 3.0 pass-through, which offers a connection port in place of the USB port used for connecting the DVI adapter – an ideal workaround for Ultrabook or laptop users where only a limited number of USB ports are available.

The USB to DVI adapter functions as an external graphics card, providing a convenient way to add multi-monitor capability to a USB 3.0-enabled desktop or laptop computer (optimal performance from USB 3.0, backward compatible with USB 2.0). The included DVI to VGA adapter also allows you to use this device with a VGA display.

Leveraging the high-bandwidth (5 Gbps) SuperSpeed USB 3.0 interface, the adapter delivers smooth, high-definition content to your DVI display / projector. The adapter can be used to mirror your primary desktop, showing the same image on each display, or to extend your desktop to double your workspace and increase your productivity.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Recommended System Requirements:

CPU: Quad Core 2.4GHz or Higher (i5 recommended)

RAM: 4GB or higher

## Certifications, Reports and Compatibility

### Applications

- The 1-Port USB hub allows the use of another USB device without losing USB connectivity on your Ultrabook or slim laptop

- Add a secondary DVI display and extend your desktop without taking apart your computer to install a new video card
- Add multi-monitor capability to a single computer, to create engaging multimedia presentations
- Run multiple applications on different screens - check your email on one display and search the web on the other
- View large or multiple spreadsheets across multiple displays
- Use the adapter to connect your PC to your DVI-equipped projector or display for viewing family pictures and movies
- Great for researchers and writers offering the ability to have reference material on one display and a working document copy on the other

## Features

- TAA Compliant
- Supports resolutions up to 1920x1200
- Built in 1-Port USB 3.0 Hub
- SuperSpeed USB 3.0 (5 Gbps) Interface, backward compatible with USB 2.0
- Quick, easy installation
- USB-powered - No external power adapter required
- Choose between Mirrored, Extended or Primary display configurations
- Driver software supports display rotation
- DVI to VGA adapter included
- Supports the use of multiple USB32DVIEH adapters on a single system (up to 5)

---

### Hardware

Warranty	2 Years
Displays Supported	1
AV Input	USB 3.0
AV Output	DVI
	VGA
Audio	No



Bus Type	USB 3.0
USB Pass-Through	Yes
Memory	16MB
Industry Standards	SuperSpeed USB 3.0, USB 2.0
Chipset ID	Trigger - T6-688SL

---

### Performance

Maximum Analog Resolutions	1920x1200
Maximum Digital Resolutions	1920x1200
Supported Resolutions	<p>Widescreen(16/32 bit):</p> <p>1920x1200, 1920x1080, 1680x1050, 1600x900, 1440x900, 1360x768, 1280x800, 1280x768, 1280x720</p> <p>Standard(16/32 bit):</p> <p>1600x1200, 1400x1050, 1280x1024, 1280x960, 1152x864, 1024x768, 800x600</p>
Wide Screen Supported	Yes
General Specifications	This USB video adapter uses a Trigger family chipset. If you're connecting this device to a computer along with additional USB video adapters or docking stations, please avoid using devices with a DisplayLink or Fresco family chipset.

---

### Connector(s)

Connector A	USB Type-A (9 pin) USB 3.0 (5 Gbps)
Connector B	DVI-I (29 pin)
	USB Type-A (9 pin) USB 3.0 (5 Gbps)

---

### Software

OS Compatibility	<p>Windows 11</p> <p>Windows 10 (32/64)</p> <p>Windows 8 / 8.1 (32/64)</p> <p>Windows 7(32/64)</p> <p>Windows Vista (32/64)</p>
------------------	---



Windows XP (32/64)

Microsoft WHQL Certified Yes

**Special Notes / Requirements**

System and Cable Requirements  
System Processor: Quad Core 2.4GHz (i5 recommended)  
System Memory: 4GB  
Not intended for gaming

Note  
This USB video adapter uses a Trigger family chipset. If you're connecting this device to a computer along with additional USB video adapters or docking stations, avoid using devices with different family chipsets, such as DisplayLink or Fresco Logic

Connect a maximum of five USB video adapters on a single computer. Support for multiple adapters will vary depending upon your system resources

This USB video adapter is not intended for graphical intensive applications, such as gaming

**Power**

Power Source USB-Powered

**Environmental**

Operating Temperature 0C to 50C (32F to 122F)

Storage Temperature -10C to 75C (14F to 167F)

Humidity < 85% non-condensing

**Physical Characteristics**

Color Black

Material Plastic

Cable Length 6.3 in [16 cm]

Product Length 3.3 in [85.0 mm]

Product Width 1.9 in [49.0 mm]

Product Height 0.7 in [17.0 mm]

Weight of Product 2.7 oz [76.0 g]



---

**Packaging  
Information**

Package Length	5.6 in [14.1 cm]
Package Width	8.2 in [20.8 cm]
Package Height	1.5 in [38.0 mm]
Shipping (Package) Weight	6.4 oz [182.0 g]

---

**What's in the Box**

Included in Package	USB 3.0 to DVI Adapter
	DVI to VGA adapter
	Software CD
	Manual

---

***\*Product appearance and specifications are subject to change without notice.***

