

2 Port HDMI Video Splitter with Audio - USB Powered

Product ID: ST122HDMILE



The ST122HDMILE 2-Port HDMI Video Splitter with Audio lets you share a single high definition video and audio source between two HDMI or DVI (with HDMI to DVI cable) displays. The HDMI splitter is USB-powered, making it ideal for use with desktop and laptop computers that offer HDMI output.

The USB powered High Speed HDMI splitter is HDCP 1.1 compliant, delivering outstanding audio capability and flawless digital video at resolutions of up to 1080p.

To overcome connection distance limitations, the HDMI splitter also functions as an HDMI distribution amplifier allowing you to situate HDMI monitors up to 45ft (15m) away from the HDMI source - a perfect solution for connecting an HDMI-capable computer to monitors, projectors or plasma screens as needed.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility

Applications

- Connecting multiple HDMI enabled projectors, LCD Displays, and Plasma Displays from a single PC source
- Ideal for classroom settings, where educators can display their computer screen on multiple displays for better visibility
- Perfect for corporate boardrooms that employ multiple screens or projectors
- · Set up your trade show display with multiple screens
- Use in retail environments for advertising or training



Features

- Splits an HDMI source to 2 outputs, without signal loss
- Integrated signal amplifier situate displays up to 45ft(15m) away
- Supports a wide range of HDTV resolutions, from 480p to 1080p
- USB-powered no wall outlet or bulky power supply required
- High Speed HDMI and HDCP 1.1 compliant
- Compact design

Hardware Warranty 2 Years Ports 2 AV Input HDMI AV Output HDMI Industry Standards High Speed HDMI, HDCP Daisy-Chain Yes Performance Maximum Cable Length Maximum Cable Length 49.2 ft [15 m] Supported Resolutions 480p, 480i, 720p, 1080i, 1080p 1600x1200(UXGA) 1600x1200(UXGA) Wide Screen Supported Yes Connector(s) Connector A HDMI (19 pin) USB Type-A (4 pin) USB 2.0 Connector B HDMI (19 pin) Special Notes / Requirements System and Cable An HDMI source (desktop / laptop) with a USB port for powering ST122LE.			
Ports 2 AV Input HDMI AV Output HDMI Industry Standards High Speed HDMI, HDCP Daisy-Chain Yes Performance Maximum Cable Length Maximum Cable Length 49.2 ft [15 m] Supported Resolutions 480p, 480i, 720p, 1080i, 1080p 1600x1200(UXGA) Wide Screen Supported Ves Yes Connector(s) Connector A Bub Type-A (4 pin) USB 2.0 USB Type-A (4 pin) USB 2.0 Special Notes / Requirements An HDMI source (desktop / laptop) with a USB port for powering	Hardware		
AV Input HDMI AV Output HDMI Industry Standards High Speed HDMI, HDCP Daisy-Chain Yes Performance Maximum Cable Length 49.2 ft [15 m] Supported Resolutions 480p, 480i, 720p, 1080i, 1080p 1600x1200(UXGA) Wide Screen Supported Yes Connector(s) Connector A BDMI (19 pin) USB Type-A (4 pin) USB 2.0 Connector B HDMI (19 pin) Special Notes / Requirements System and Cable An HDMI source (desktop / laptop) with a USB port for powering		Warranty	2 Years
AV Output HDMI Industry Standards High Speed HDMI, HDCP Daisy-Chain Yes Performance Maximum Cable Length 49.2 ft [15 m] Supported Resolutions 480p, 480i, 720p, 1080i, 1080p 1600x1200(UXGA) Wide Screen Supported Yes Connector(s) Connector A HDMI (19 pin) USB Type-A (4 pin) USB 2.0 USB Type-A (4 pin) USB 2.0 Special Notes / Requirements System and Cable An HDMI source (desktop / laptop) with a USB port for powering		Ports	2
Industry Standards High Speed HDMI, HDCP Daisy-Chain Yes Performance Maximum Cable Length 49.2 ft [15 m] Supported Resolutions 480p, 480i, 720p, 1080i, 1080p 1600x1200(UXGA) 1600x1200(UXGA) Wide Screen Supported Yes Connector(s) Connector A HDMI (19 pin) USB Type-A (4 pin) USB 2.0 Connector B HDMI (19 pin) Special Notes / Requirements System and Cable An HDMI source (desktop / laptop) with a USB port for powering		AV Input	HDMI
Daisy-Chain Yes Performance Maximum Cable Length 49.2 ft [15 m] Supported Resolutions 480p, 480i, 720p, 1080i, 1080p 1600x1200(UXGA) 1600x1200(UXGA) Wide Screen Supported Yes Connector(s) Connector A Description USB Type-A (4 pin) USB 2.0 Connector B HDMI (19 pin) Special Notes / System and Cable System and Cable An HDMI source (desktop / laptop) with a USB port for powering		AV Output	HDMI
Performance Maximum Cable Length 49.2 ft [15 m] Supported Resolutions 480p, 480i, 720p, 1080i, 1080p 1600x1200(UXGA) 1600x1200(UXGA) Wide Screen Supported Yes Connector(s) Connector A HDMI (19 pin) USB Type-A (4 pin) USB 2.0 Connector B HDMI (19 pin) Special Notes / Requirements System and Cable An HDMI source (desktop / laptop) with a USB port for powering		Industry Standards	High Speed HDMI, HDCP
Maximum Cable Length 49.2 ft [15 m] Supported Resolutions 480p, 480i, 720p, 1080i, 1080p 1600x1200(UXGA) Wide Screen Supported Yes Connector(s) Connector A HDMI (19 pin) USB Type-A (4 pin) USB 2.0 Connector B HDMI (19 pin) Special Notes / Requirements System and Cable An HDMI source (desktop / laptop) with a USB port for powering		Daisy-Chain	Yes
Supported Resolutions 480p, 480i, 720p, 1080i, 1080p 1600x1200(UXGA) Wide Screen Supported Yes Connector(s) Connector A HDMI (19 pin) USB Type-A (4 pin) USB 2.0 Connector B HDMI (19 pin) Special Notes / Requirements System and Cable An HDMI source (desktop / laptop) with a USB port for powering	Performance		
1600x1200(UXGA) Wide Screen Supported Yes Connector(s) Connector A HDMI (19 pin) USB Type-A (4 pin) USB 2.0 Connector B HDMI (19 pin) Special Notes / Requirements System and Cable An HDMI source (desktop / laptop) with a USB port for powering		Maximum Cable Length	49.2 ft [15 m]
Wide Screen Supported Yes Connector(s) Connector A HDMI (19 pin) USB Type-A (4 pin) USB 2.0 USB Type-A (4 pin) USB 2.0 Connector B HDMI (19 pin) Special Notes / Requirements System and Cable An HDMI source (desktop / laptop) with a USB port for powering		Supported Resolutions	480p, 480i, 720p, 1080i, 1080p
Connector(s) Connector A HDMI (19 pin) USB Type-A (4 pin) USB 2.0 Connector B HDMI (19 pin) Special Notes / Requirements System and Cable An HDMI source (desktop / laptop) with a USB port for powering			1600x1200(UXGA)
Connector A HDMI (19 pin) USB Type-A (4 pin) USB 2.0 Connector B HDMI (19 pin) Special Notes / Requirements System and Cable An HDMI source (desktop / laptop) with a USB port for powering		Wide Screen Supported	Yes
USB Type-A (4 pin) USB 2.0 Connector B HDMI (19 pin) Special Notes / Requirements System and Cable An HDMI source (desktop / laptop) with a USB port for powering	Connector(s)		
Connector B HDMI (19 pin) Special Notes / Requirements System and Cable An HDMI source (desktop / laptop) with a USB port for powering		Connector A	HDMI (19 pin)
Special Notes / Requirements System and Cable An HDMI source (desktop / laptop) with a USB port for powering			USB Type-A (4 pin) USB 2.0
Requirements System and Cable An HDMI source (desktop / laptop) with a USB port for powering		Connector B	HDMI (19 pin)
System and Cable An HDMI source (desktop / laptop) with a USB port for powering			
	-		An HDMI source (desktop / laptop) with a USB port for powering ST122LE.



Indicators	LED Indicators	Power
Power		
	Power Source	USB-Powered
	Input Voltage	5 DC
	Input Current	500mA
Environmental		
	Operating Temperature	0C to 70C (32F to 158F)
	Storage Temperature	-20C to 85C (-4F to 185F)
	Humidity	0~95% RH
Physical Characteristics		
	Color	Black
	Material	Plastic
	Cable Length	11.0 in [28 cm]
	Product Length	3.0 in [75.0 mm]
	Product Width	2.0 in [50.0 mm]
	Product Height	1.0 in [25.0 mm]
	Weight of Product	2.7 oz [76.0 g]
Packaging Information		
	Package Length	8.3 in [21.0 cm]
	Package Width	5.7 in [14.5 cm]
	Package Height	1.6 in [40.0 mm]
	Shipping (Package) Weight	7.7 oz [219.0 g]
What's in the Box	Included in Package	HDMI Splitter
		24" USB Power cable



Instruction Manual

*Product appearance and specifications are subject to change without notice.

