

4-port HDMI splitter and signal amplifier

Product ID: ST124HDMI2



The ST124HDMI2 4 Port High Speed HDMI Video Splitter with Audio lets you share a single HDMI source with up to 4 HDMI or DVI-D enabled displays/receivers, without sacrificing image or sound quality. Mounting brackets are included for a tidy, professional installation.

Supporting true HD video resolutions up to 1080p, this HDMI splitter allows you to situate your HDMI-capable displays up to 50 ft (15.2 m) away from the splitter. This versatile HDMI splitter features 3.5mm audio input and output connections giving you the option of sending your accompanying audio signal through the HDMI cable or through a separate 3.5mm stereo audio channel.

A perfect addition to virtually any application requiring the high quality video delivered by HDMI devices, the ST124HDMI2 video splitter is easy to install and provides flawless, distortion-free digital video.

This product is TAA compliant and backed by a Startech.com 2-year warranty with free lifetime technical support.

## **Certifications, Reports and Compatibility**

## **Applications**

- Connect HDMI enabled projectors, monitors, plasma screens, commercial billboards, and wall display systems
- Ideal for business conference rooms and trade show displays
- Perfect for classrooms and business multimedia presentations
- · Great for digital signage applications displaying video advertisements with audio in retail environments
- Financial applications include stock tickers or promotion of new products/services



• Display information in waiting rooms or to patients in healthcare facilities

## Features

- Splits a single HDMI source to up to 4 HDMI-enabled devices without signal loss
- Supports a wide range of PC and Supports HDTV resolutions from VGA to WUXGA and 480p to 1080p
- Mounting brackets included
- Audio signal can be output through HDMI or using separate 3.5mm audio outputs
- High Speed HDMI Compliant
- Passes DVI video signals, DVI to HDMI adapters/cables required not included
- Cascade up to 3 layers
- Supports HDCP and EDID
- LED Power/Active indicator for monitoring each port
- Quick and easy install

Hardware		
	Warranty	2 Years
	Ports	4
	AV Input	HDMI
	AV Output	HDMI
	Cabling	HDMI
	Audio	Yes
	Industry Standards	High Speed HDMI, HDCP, EDID
	Daisy-Chain	Yes
Performance		
	Maximum Cable Length	50.0 ft [15.2 m]
	Maximum Digital Resolutions	HDTV 1080p / PC 1920x1200
	Supported Resolutions	1080p (1920 x 1080) / VGA (640 x 480) / SXGA (1280 x 1024) / UXGA (1600 x 1200) / WUXGA (1920 x 1200)



	Wide Screen Supported	Yes
Connector(s)	Connector A	3.5 mm Mini-Jack (3 Position)
		HDMI (19 pin)
	Connector B	3.5 mm Mini-Jack (3 Position)
		HDMI (19 pin)
Indicators	LED Indicators	Power (Green) / Input Signal (Blue)
		Green Port signal indicator
Power	D	
	Power Source	AC Adapter Included
	Input Voltage	100 - 240 AC
	Input Current	0.8A
	Output Voltage	12V DC
	Output Current	1.5A
	Center Tip Polarity	Positive
	Plug Type	Μ
	Power Consumption (In Watts)	18
Environmental		
	Operating Temperature	0C to 40C (32F to 104F)
	Storage Temperature	-20C to 60C (-4F to 140F)
	Humidity	0%~80%
Physical Characteristics		
	Color	Black
	Material	Steel



		instruction manual
		universal power adapter (NA / EU / UK / AU)
		mounting hardware and screw kit
	Included in Package	HDMI splitter
What's in the Box		
	Shipping (Package) Weight	4.3 lb [2.0 kg]
	Package Height	3.5 in [90 mm]
	Package Width	16.2 in [41.1 cm]
	Package Length	8.4 in [21.4 cm]
Packaging Information		
	Weight of Product	34.1 oz [966 g]
	Product Height	1.7 in [44 mm]
	Product Width	5.3 in [13.5 cm]
	Product Length	8.7 in [22 cm]

\*Product appearance and specifications are subject to change without notice.