

VGA to HDMI Adapter with USB Audio & Power – Portable VGA to HDMI Converter – 1080p

Product ID: VGA2HDU



The VGA2HDU VGA to HDMI adapter lets you turn the VGA port on your Desktop or Laptop computer into an HDMI output port.

With the VGA2HDU, you can expand your VGA video output to accommodate the increasing number of displays and projectors that only support HDMI.

Not all VGA converters are created equal. This adapter ensures you're harnessing the highest video quality from your VGA output, with support for resolutions up to 1920x1080 (1080p).

For hassle-free setup the VGA to HDMI adapter allows for plug-and-play installation. Plus, with a built-in USB power cable the device is powered using the USB port on your computer. The VGA to HDMI adapter will work with any computer operating system, but when working with a Windows computer the adapter supports native USB audio, allowing you to add your computer audio to the HDMI signal.

The VGA2HDU is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Connect your VGA-equipped computer to an HDMI home theatre system
- Share video content from your VGA-equipped computer on an HDMI television or projector



- Connect a legacy VGA-equipped device to a newer HDMI display
- Share audio from your Windows based PC

Features

- Supports video resolutions up to 1920x1080
- Plug-and-play installation
- USB powered
- USB audio
- Compact, lightweight design

Hardware		
	Warranty	2 Years
	Active or Passive Adapter	Active
	AV Input	VGA
	AV Output	HDMI
	Cabling	HDMI
	Audio	Yes
	Chipset ID	MacroSilicon - MS9282
Performance		
	Maximum Analog Resolutions	1920x1080
	Maximum Digital Resolutions	1920x1080
	Supported Resolutions	1920x1080 (1080p)
		1680x1050 (WSXGA+)
		1600x1200
		1600x900
		1440x900
		1400x1050 (SXGA+)
		1366x768



		1360x768
		1280x1024
		1280x960
		1280x800
		1280x768 (WXGA)
		1280x720p (720p)
		1280x600
		1152x864
		1024x768
		800x600 (SVGA)
		640x480 (480p)
	Wide Screen Supported	Yes
	MTBF	1,063,669 hours
Connector(s)		
	Connector A	1 - VGA (15 pin, High Density D-Sub)
		1 - USB 2.0 Type-A (4 pin, 480Mbps)
	Connector B	1 - HDMI (19 pin)
Special Notes / Requirements		
	Note	When used with a Windows computer this adapter supports native USB audio.
		If used with a computer, volume levels cannot be adjusted using the operating system. Volume levels can be controlled by the output device (TV, speakers, audio receiver, etc).
Power	Power Source	USB-Powered
Environmental		
Invironmental	Operating Temperature	0C to 60C (32F to 140F)
	Storogo Tomporaturo	-10C to 70C (14F to 158F)
	Storage Temperature	





Physical Characteristics

Ondracteristics	Color	Black
	Material	Plastic
	Product Length	9.8 in [25.0 cm]
	Product Width	1.4 in [3.5 cm]
	Product Height	0.5 in [1.3 cm]
	Weight of Product	2.4 oz [69.0 g]
Packaging Information		
	Package Quantity	1
	Package Length	8.7 in [22.0 cm]
	Package Width	5.0 in [12.8 cm]
	Package Height	0.5 in [1.3 cm]
	Shipping (Package) Weight	2.4 oz [69.0 g]
What's in the Box		
	Included in Package	1 - VGA to HDMI adapter w/ USB power & audio
		1 - 2ft USB Extension Cable
		1 - Instruction Manual

*Product appearance and specifications are subject to change without notice.

