19" 16 PORT HDMI USB KVM DRAWER

BRAND: PRITECH

PART NO. : PA-HT1916



OVERVIEW

The PA-HT1916 1U KVM switch with monitor integrates a 19" LCD screen, keyboard & touchpad, and a 16 ports HDMI USB KVM switch in a 1U compact design. The 16 port lcd switch can control 16 computers with one USB monitor, keyboard and mouse.

The PA-HT1916 LCD KVM console supports high video quality up to 1280 x 1024@60Hz. Switching between computers can be easily accomplished by panel pushbuttons, keyboard hotkey combination, on-screen-display (OSD) and mouse.

The KVM switch supports USB connections for the computers. An extra HDMI port allows an additional HDMI monitor to be connected.

FEATURES

FEATURES

- Integrated rack mount drawer with 19" rackmount keyboard and monitor/touchpad and 16 port KVM in a 1U height console
- Standard HDMI connection-Connect to a server or computer via standard HDMI connectors
- LCD module can be opened up to 108 degrees to provide a comfortable viewing angle
- Support computers with USB keyboard and mouse

MANAGEMENT

- Convenient computer switching via front panel LEDs, keyboard hotkey combination or on-screen-display (OSD)
- Auto scan feature for monitoring user-selected computer
- Broadcast mode--operations simultaneously performed on all selected computers
- Hot pluggable --add or remove computers without having to power down the switch
- Quickly select your computer by naming the server or inputting SN number of the server
- On-Screen Display (OSD) adjustments-Adjust the on-screen image, including: auto adjust, exit, power on/off, brightness, menu, and a power indicator

HIGH RESOLUTION

- 19" TFT LCD monitor with highlight, high definition and high resolution
- Resolution is up to 1280x 1024 60Hz

SECURITY

- Two level password security--only authorized users view and control computers
- Supports one administrator and four user accounts with a separate profile for each

HIGH PERFORMANCE TOUCHPAD

• Touchpad with scroll wheel - Eliminates the need for a separate, external mouse

KEYBOARD

- Multi-language support--English, Russian, German, French, Spanish, and Korean etc.
- Full size 99 keys keyboard with integrated number pad


WIDE COMPATIBILITY

- Multiplatform Support-Compatible with Windows, Sun, Unix and Linux
- Supports servers form Lenovo, HUA WEI, HP, IBM, Cisco and Dell, etc.

SPECIFICATIONS

COMPUTER CONNECTIONS Direct Max 16 Max 16 PORT EMULATION Keyboard, mouse USB LCD MONITOR LCD model SXGA TFT View area 19" Optimum resolution Display colour Brightness 250cd/m² (T y p) Contrast ratio 1000: 1 (T y p) Pixel pitch(mm) Roll wheel Supports scroll wheel function KEYBOARD KEYBOARD REYBOARD Supports scroll wheel function Front panel pushbuttons, hotkeys, OSD menu INPUT POWER POWER CONSUMPTION OPERATING TEMPERATURE O—50 °C STORE TEMPERATURE USB SXGA TFT 108 108 SXGA TFT 109" 1000: 1 (T y p) 0.2928(H) × 0.2928(W) 1000: 1 (T y p) 0.2928(H) × 0.2928(W) 1000: 1 (T y p) Pixel pitch(mm) Supports scroll wheel function 99 keys (82 keys main keyboard +17 independent small numeric keyboard) Front panel pushbuttons, hotkeys, OSD menu 1000: 240Vac, 50-60Hz, <1.5A POWER CONSUMPTION OPERATING TEMPERATURE -20—60 °C	Model		PA-HT1916
PORT EMULATION CODE CODE	ER CONNECTIONS	Direct	16
LCD MONITOR LCD model SXGA TFT View area 19" Optimum resolution 1280×1024@60Hz Pisplay colour 16.7 M Brightness 250cd/m² (Typ) Contrast ratio 1000:1 (Typ) Pixel pitch(mm) 0.2928(H) × 0.2928(W) MOUSE X/Y resolution >1000 points /inch, (40 points/mm) Roll wheel Supports scroll wheel function KEYBOARD 99 keys (82 keys main keyboard +17 independent small numeric keyboard) PORT SELECTION Front panel pushbuttons, hotkeys, OSD menu INPUT POWER 100V- 240Vac, 50-60Hz, <1.5A POWER CONSUMPTION 25W OPERATING TEMPERATURE 0—50 °C STORE TEMPERATURE -20—60 °C	1	Лах	16
View area 19"	ULATION F	Keyboard, mouse	USB
Optimum resolution Display colour 16.7 M Brightness 250cd/m² (Typ) Contrast ratio 1000: 1 (Typ) Pixel pitch(mm) 0.2928(H) × 0.2928(W) MOUSE X/Y resolution Roll wheel Supports scroll wheel function KEYBOARD 99 keys (82 keys main keyboard +17 independent small numeric keyboard) PORT SELECTION Front panel pushbuttons, hotkeys, OSD menu INPUT POWER 100V- 240Vac, 50-60Hz, <1.5A POWER CONSUMPTION 25W OPERATING TEMPERATURE 0—50 °C STORE TEMPERATURE	IITOR L	.CD model	SXGA TFT
resolution Display colour Display Ci y p) D	\	/iew area	19"
Brightness 250cd/m² (Typ) Contrast ratio 1000: 1 (Typ) Pixel pitch(mm) 0.2928(H) × 0.2928(W) MOUSE X/Y resolution >1000 points /inch, (40 points/mm) Roll wheel Supports scroll wheel function KEYBOARD 99 keys (82 keys main keyboard +17 independent small numeric keyboard) PORT SELECTION Front panel pushbuttons, hotkeys, OSD menu INPUT POWER 100V- 240Vac, 50-60Hz, <1.5A POWER CONSUMPTION 25W OPERATING TEMPERATURE 0—50 °C STORE TEMPERATURE -20—60 °C		-	1280×1024@60Hz
Contrast ratio Pixel pitch(mm) O.2928(H) × 0.2928(W) X/Y resolution Roll wheel Supports scroll wheel function KEYBOARD 99 keys (82 keys main keyboard +17 independent small numeric keyboard) PORT SELECTION Front panel pushbuttons, hotkeys, OSD menu INPUT POWER 100V- 240Vac, 50-60Hz, <1.5A POWER CONSUMPTION 25W OPERATING TEMPERATURE 0—50 °C STORE TEMPERATURE -20—60 °C	[Display colour	16.7 M
Pixel pitch(mm) O.2928(H) × O.2928(W) MOUSE X/Y resolution Roll wheel Supports scroll wheel function KEYBOARD 99 keys (82 keys main keyboard +17 independent small numeric keyboard) PORT SELECTION Front panel pushbuttons, hotkeys, OSD menu INPUT POWER 100V- 240Vac, 50-60Hz, <1.5A POWER CONSUMPTION 25W OPERATING TEMPERATURE 0—50 °C STORE TEMPERATURE -20—60 °C	E	Brightness	250cd/m ² (T y p)
MOUSE X/Y resolution Roll wheel Supports scroll wheel function Supports scroll wheel function 99 keys (82 keys main keyboard +17 independent small numeric keyboard) PORT SELECTION Front panel pushbuttons, hotkeys, OSD menu INPUT POWER 100V- 240Vac, 50-60Hz, <1.5A POWER CONSUMPTION 25W OPERATING TEMPERATURE 0—50 °C STORE TEMPERATURE -20—60 °C	(Contrast ratio	1000:1 (Typ)
Roll wheel Supports scroll wheel function 99 keys (82 keys main keyboard +17 independent small numeric keyboard) PORT SELECTION Front panel pushbuttons, hotkeys, OSD menu INPUT POWER 100V- 240Vac, 50-60Hz, <1.5A POWER CONSUMPTION 25W OPERATING TEMPERATURE 0—50 °C STORE TEMPERATURE -20—60 °C	F	Pixel pitch(mm)	0.2928(H) × 0.2928(W)
KEYBOARD 99 keys (82 keys main keyboard +17 independent small numeric keyboard) PORT SELECTION Front panel pushbuttons, hotkeys, OSD menu INPUT POWER 100V- 240Vac, 50-60Hz, <1.5A POWER CONSUMPTION 25W OPERATING TEMPERATURE 0-50 °C STORE TEMPERATURE -20-60 °C	MOUSE	(/Y resolution	>1000 points /inch, (40 points/mm)
(82 keys main keyboard +17 independent small numeric keyboard) PORT SELECTION Front panel pushbuttons, hotkeys, OSD menu INPUT POWER 100V- 240Vac, 50-60Hz, <1.5A POWER CONSUMPTION 25W OPERATING TEMPERATURE 0—50 °C STORE TEMPERATURE -20—60 °C	F	Roll wheel	Supports scroll wheel function
PORT SELECTIONFront panel pushbuttons, hotkeys, OSD menuINPUT POWER100V- 240Vac, 50-60Hz, <1.5A	KEYBOARD		(82 keys main keyboard +17 independent small numeric
POWER CONSUMPTION 25W OPERATING TEMPERATURE 0-50 °C STORE TEMPERATURE -20-60 °C	PORT SELECTION		
OPERATING TEMPERATURE 0—50 °C STORE TEMPERATURE -20—60 °C	INPUT POWER		100V- 240Vac, 50-60Hz, <1.5A
STORE TEMPERATURE -20—60 °C	POWER CONSUMPTION		25W
	OPERATING TEMPERATURE		0—50 °C
	STORE TEMPERATURE		-20—60 °C
HUMIDITY 0—80% RH, non-condensing	HUMIDITY		0—80% RH, non-condensing
NET WEIGHT 13.6kg	NET WEIGHT		13.6kg
PRODUCT DIMENSION (W × D × H) 448mm×605mm×42.5mm	PRODUCT DIMENSION (W × D × H)		448mm×605mm×42.5mm
PACKAGE DIMENSION (W × D × H) 765mm×615mm×185mm	PACKAGE DIMENSION (W × D × H)		765mm×615mm×185mm
OPTIONAL POWER INPUT -36V— -72V DC	OPTIONAL POWER INPUT		-36V— -72V DC

DIAGRAM





PRITECH AUTOMATION PRIVATE LIMITED

PHONE : +91 79 27702711, 09714854011

: sales@pritechautomation.com **EMAIL**

WEBSITE : www.pritechautomation.com















