

19" 32 PORT USB HDMI KVM DRAWER

BRAND : PRITECH
PART NO. : PA-HT1932



OVERVIEW

The PA-HT1932 rack lcd console integrates a 19" LCD monitor, a keyboard/touchpad and a Cat6 KVM switch in a 1U rack mount housing.

The PA-HT1932 allows access and control up to 32 computers from a single console (keyboard, mouse, and monitor). When cascading to another 31 KVM Switches, a single PA-HT1932 can control up to 1024 computers.

The PA-HT1932 has a built-in 19" LCD monitor that supports resolution up to 1280x1024@60Hz. For added convenience, two USB ports and one VGA port are included in the rear of the KVM unit allow for connection of keyboard/mouse and external display.

With the PA-HT1932, you can switch easily between computers by front panel pushbuttons, OSD (on-screen display) or keyboard hotkey command. To enhance security, the PA-HT1932 provides two-level password security which prevents unauthorized users to viewing and controlling the connected computers.

With RJ-45 connectors and Cat6 cables connected to computers, the PA-HT1932 helps extend the distance to the servers up to 100m.

FEATURES

HARDWARE FEATURES

- Integrated KVM switch with lcd display, keyboard/touchpad in a 1U height console
- Standard Cat6 Connection-Connect to a server or computer via standard RJ-45 connectors and Cat6 cables
- LCD module can be opened up to 108 degrees to provide a comfortable viewing angle
- Support computers with USB keyboard and mouse

MANAGEMENT

- Convenient computer switching via front panel LEDs, keyboard hotkey combination or on-screen-display (OSD)
- Auto scan feature for monitoring user-selected computer
- Broadcast mode--operations simultaneously performed on all selected computers
- Hot pluggable --add or remove computers without having to power down the switch
- Quickly select your computer by naming the server or inputting SN number of the server
- On-Screen Display (OSD) adjustments-Adjust the on-screen image, including: auto adjust, exit, power on/off, brightness, menu, and a power indicator

HIGH RESOLUTION

- 19" TFT LCD monitor with highlight, high definition and high resolution
- Resolution is up to 1280 x 1024 @60Hz

CASCADING CONNECTION

- By cascading up to another 31 switches, as many as 1024 servers can be controlled from a single console

SECURITY

- Two level password security--only authorized users view and control computers
- Supports one administrator and four user accounts with a separate profile for each

HIGH PERFORMANCE TOUCHPAD

- Touchpad with scroll wheel - Eliminates the need for a separate, external mouse

KEYBOARD

- Multi-language support--English, Russian, German, French, Spanish, and Korean etc.
- Full size 99 keys keyboard with integrated number pad


WIDE COMPATIBILITY

- Multiplatform Support-Compatible with Windows, Sun, Unix and Linux
- Supports servers form Lenovo, HUA WEI, HP, IBM, Cisco and Dell, etc.

SPECIFICATIONS

| Model | | PA-HT1932 |
|--------------------------------------|--|---|
| COMPUTER CONNECTIONS | Direct | 32 |
| | Max | 1024 |
| PORT EMULATION | Keyboard, mouse | PS/2, USB |
| LCD MONITOR | LCD model | SXGA TFT |
| | View area | 19" |
| | Optimum resolution | 1280×1024@60Hz |
| | Display colour | 16.7 M |
| | Brightness | 250cd/m ² (T y p) |
| | Contrast ratio | 1000: 1 (T y p) |
| | Pixel pitch(mm) | 0.2928(H) × 0.2928(W) |
| MOUSE | X/Y resolution | >1000 points / inch, (40 points/mm) |
| | Touchpad with scroll wheel | Eliminates the need for an external mouse |
| KEYBOARD | 99 keys (82 keys main keyboard +17 independent small number pad) | |
| PORT SELECTION | Front panel pushbuttons, hotkeys, On-Screen Display (OSD) | |
| INPUT POWER | 100V- 240Vac, 50-60Hz, <1.5A | |
| POWER CONSUMPTION | 23W | |
| OPERATING TEMPERATURE | 0 — 50 °C | |
| STORE TEMPERATURE | -20 — 60 °C | |
| HUMIDITY | 0~80% RH, non-condensing | |
| NET WEIGHT | 13.6kg | |
| PRODUCT DIMENSION (W × D × H) | 448mm×605mm×42.5mm | |
| PACKAGE DIMENSION (W × D × H) | 765mm×615mm×185mm | |
| OPTIONAL POWER INPUT | -36V~ -72V DC | |

DIAGRAM



PRITECH AUTOMATION PRIVATE LIMITED

PHONE : +91 79 27702711, 09714854011

EMAIL : sales@pritechautomation.com

WEBSITE : www.pritechautomation.com



ISO 9001:2015